

MEI CASHFLOW™ 330



A new concept in coin management One build standard for all markets

The CASHFLOW™ acceptor can be adapted to suit most acceptor applications and forms the core module in the highly successful range of CASHFLOW™ this compact yet powerful unit is the smallest high performance acceptor available today. It can accept up to 12 coins and is compatible with our current MS/ME range of products. Various accessories are available which include Front Plates and different electronic Interfaces.

Reliability

The CASHFLOW™ range of products continue to build on our reputation for reliability and quality. An extra wide "throat" and parallel-opening flight deck virtually eliminate coin jams. Intelligent design of coin flight minimizes the effect of dirt or moisture contamination. The latest advances in electronic integration (ASICS and SMD) ensure minimum component count and more reliable operation. Automated manufacture generates reliability in the field.

Security

With its unique mechanical design and intelligent sensing algorithms, CASHFLOW™ acceptors can provide accurate, reliable validation. Patented devices stabilize and direct coin flight to enable the most precise and accurate coin measurement in all environments.

Flexibility

CASHFLOW™ acceptors are designed to meet the changing needs of dynamic operating environments. New coin introductions, coin set changes and security upgrades can be handled with minimal effort.

mei | cashflow™
330

MEI CASHFLOW™ 330

Technical Specification

Interfaces

	Standard 112	Standard 124	Standard 212	Standard 312	Dual Polarity
Series/Parallel	Parallel	Parallel	Parallel	Parallel	Parallel
Compatibility	MS 130 Series	MS 130 Series	4" Acceptor Application	4" Acceptor Application	MS/ME111 MS 115
Voltage	12V	24V	+12V	+12V	12V
No. Coins Acc.	12	12	12	12	12
No. Coin Outputs	6	6	6	4	6
Connector Style	16 Pin DIL	16 Pin DIL	10 Pin DIL	10 Pin SIL	17 Pin SIL

Accessories

4 digit LCD credit display

Motorised reject (used with the 4" channel)

Dimensions

4" Acceptor

H: 101.6mm W: 100mm D: 49.5mm

MMI Interfaces

Standard 112 (OV Common 12V)

Standard 124 (OV Common 24V)

- 6 coin output lines
- 6 individual inhibit inputs
- An all inhibit input
- A flight deck open (ER) output
- A route inhibit inputs
- F coin inhibit or alarm output modes

Standard 212 (OV Common 12V)

- Operates from +12V supply
- 6 coin output lines
- All inhibit input
- A flight deck open (ER) output

Standard 312 (OV Common 12V)

- 4 coin outputs
- Alarm output or inhibit input
- An all inhibit input

Dual Polarity (12V)

- 6 coin output lines
- An output common
- 6 individual inhibit inputs and power connections

Why choose MEI?

MEI has focused continuously on the needs of the vending industry for the last 30 years; this industry has seen innovation, invention and dedication passed from MEI to the vending world.

MEI is one of the largest manufacturers of electronic coin changegivers, bill acceptors, cashless payment systems and other unattended transaction systems. Over a billion transactions are made every week in 90 different countries using products from MEI.

MEI UNITED KINGDOM/EUROPE
Unit 51/52, Suttons Business Park,
Suttons Park Avenue, Earley,
Reading, Berkshire RG6 1AZ
Tel: +44 845 0944 370
Fax: +44 118 907 4060

MEI UNITED STATES
1301 Wilson Drive
West Chester, PA 19380
Tel: +1 610 430 2500
Fax: +1 610 430 2694

MEI AUSTRALIA
Level 9, Avaya House, 123 Epping
Road, North Ryde, NSW 2113,
Australia
Tel: +61 2 8875 7753
Fax: +61 2 8875 7957

MEI MEXICO
S. de R.L. de C.V
Av. Santa Rosa de Viterbo 10
Parque Industrial Finsa-Queretaro
El Marques, Queretaro CP 76246
Tel: +52 442 238 2000
Fax: +52 442 238 2001



mei
www.meigroup.com